

LRD 2983

WORK LIGHT LRD 2983 SLIM

DANE TECHNICZNE

| | | |
|---------------------------|--------------------|---|
| Light colour | Light group | Light category |
| white | HOR 73 | working light |
| Ingress protection rating | LED light | LED quantity |
| IP 68 | yes | 6 |
| Power rating | Supply voltage | Cable |
| 23 W | 12/24 V | 2×0,75 mm ² ; cable length 1,5 m |
| Connection method | Side | Luminous flux |
| screw-on | universal | 1800 lm |
| Dispersed light | Colour temperature | Operating temperature range |
| yes | 6500 K | from -30°C to +50°C |

OPIS

The range of Horpol work lights has been expanded with products in the SLIM version: LRD 2983, LRD 2984 with a reversing function and LRD 2985 with a magnetic assemble base and a cigarette lighter plug. The LRD 2983 SLIM work lamp is distinguished by the comfort of using the lamp and the optimal combination of technical parameters. The housing itself is made of aluminum, facilitating heat dissipation. The tilted support allows you to change the angle of inclination of the lamp, and thus the light distribution. Like other Horpol work lights, also SLIM lamps are equipped with LED diodes. The field of work is illuminated by 6 LEDs with a cold color, pleasant to the eye during night work. LRD lamps are completely resistant to cracks and impacts, extremely durable in contact with dirt and moisture.