

## LRD 2679/RED

WORK LIGHT LRD 2679/RED

DANE TECHNICZNE

Light group	Light category	LED light
HOR 111	working light	yes
LED quantity	Dispersed light	Side
15	yes	universal
Connection method	Supply voltage	Power rating
screw-on	12/24 V	3,6 W
Cable	Operating temperature range	Light colour
2×0,75 mm <sup>2</sup> ; cable length 1,5 m	from -30°C to +50°C	red
Luminous flux	Ingress protection rating	Wavelength of light
100 lm	IP 68	628 nm

### OPIS

**LRD 2679/RED work lamp - red light for special tasks.** The LRD 2679/RED lamp is a compact and efficient source of **diffused red light**, designed for operation in demanding conditions. With a power output of **3,6 W** and a **luminous flux of 100 lm**, it provides comfortable illumination of the work area without dazzling the operator or others nearby. Its **universal operating voltage (12/24 V)** and flexible mounting options allow for easy installation on various vehicles and machines. The durable housing and **IP 68 protection rating** ensure reliable performance even in extreme environments – mud, dust, rain, or snow pose no threat. The lamp meets **R10 (EMC)** standards, meaning it does not interfere with the vehicle's electronic systems. It can operate within a wide temperature range, making it a perfect all-season solution. The LRD 2679/RED lamp is ideal for service and road vehicles, where the red light effectively marks the working zone, enhancing safety in road traffic and during nighttime operations.

