

LRD 2679/RED

WORK LIGHT LRD 2679/RED

DANE TECHNICZNE

Light colour	Light group	Light category
red	HOR 111	working light
Ingress protection rating	LED light	LED quantity
IP 68	yes	15
Power rating	Supply voltage	Cable
3,6 W	12/24 V	2×0,75 mm ² ; cable length 1,5 m
Connection method	Side	Luminous flux
screw-on	universal	100 lm
Dispersed light	Wavelength of light	Operating temperature range
yes	628 nm	from -30°C to +50°C

OPIS

LRD 2679/RED work lamp - red light for special tasks. The LRD 2679/RED lamp is a compact and efficient source of **diffused red light**, designed for operation in demanding conditions. With a power output of **3,6 W** and a **luminous flux of 100 lm**, it provides comfortable illumination of the work area without dazzling the operator or others nearby. Its **universal operating voltage (12/24 V)** and flexible mounting options allow for easy installation on various vehicles and machines. The durable housing and **IP 68 protection rating** ensure reliable performance even in extreme environments – mud, dust, rain, or snow pose no threat. The lamp meets **R10 (EMC)** standards, meaning it does not interfere with the vehicle's electronic systems. It can operate within a wide temperature range, making it a perfect all-season solution. The LRD 2679/RED lamp is ideal for service and road vehicles, where the red light effectively marks the working zone, enhancing safety in road traffic and during nighttime operations.