

# LCD 3241

REVERSING LIGHT LCD 3241  
DANE TECHNICZNE

Light colour	Light group	Light category
white	HOR 128	reversing
Ingress protection rating	LED light	LED quantity
IP 68	yes	6
Power rating	Supply voltage	Cable
2,5 W	12/24 V	2×0,75 mm <sup>2</sup> ; cable length 0,5 m
Side	Reversing light	Operating temperature range
universal	yes	from -30°C to +50°C

## OPIS

The **LCD 3241 reversing light** is an energy-efficient LED lighting solution that ensures excellent visibility during maneuvers. Equipped with **6 LEDs**, it emits high-intensity **white light**, meeting the **R148** and **R10** approval requirements. **Key features:** - Compatible with various means of transport - the light operates within a **12/24 V** range, making it suitable for different types of vehicles. - Energy-efficient performance - with a rated power of **2,5 W**, it provides optimal efficiency while consuming minimal energy. - Superior durability - its **IP 68** rating guarantees protection against dust and water, making it ideal for use in harsh conditions. - **Wide operating temperature range** - the light functions effectively even in extreme temperatures, enhancing its versatility. - **Complete mounting kit included** - the package contains mounting screws and caps. - **Flexible installation options** - can be installed with or without a holder, allowing for better adaptability to user preferences. Choose safety and durability - LCD 3241 by [Horpol](#)!



Horpol  
NIP:

