

## LRD 3072

### WORK LIGHT LRD 3072

### DANE TECHNICZNE

Light group	Light category	LED light
HOR 142	working light	yes
LED quantity	Dispersed light	Side
6	yes	universal
Connection method	Supply voltage	Power rating
screw-on	12/24 V	10 W
Cable	Operating temperature range	Light colour
2x0,5 mm <sup>2</sup> ; cable length 1,5 m, round, 2x0,75 mm <sup>2</sup> ; cable length 1,5 m, round	from -30°C to +50°C	white
Colour temperature	Luminous flux	Ingress protection rating
5600 K	1200 lm	IP 68

### OPIS

The **LRD 3072** work lamp is a reliable and efficient solution with perfect combination of technical parameters. Equipped with **6 LEDs**, it generates **dispersed**, white light with a color temperature of **5600 K** and an impressive luminous flux of **1200 lm**. The white light provides a further distance (**8 m**) and a wider range of lighting, increasing visibility to ensure safe driving and working in the late evening hours. The tilting support allows the possibility of changing the angle of the lamp, and thus the light distribution. Thanks to the universal supply voltage (**12/24 V**) and nominal power of **10 W**, the lamp is perfect for various applications, in difficult atmospheric and industrial conditions. The lamp is completely resistant to mechanical damage, extremely durable in contact with dirt and moisture (ingress protection rating **IP 68**). The operation of the lamp is also guaranteed in a way that does not emit electromagnetic interference and is electromagnetic interference-resistant, which is confirmed by the **EMC certificate**. **The HOR 142 lamp group also includes:** - Work lamp with warning light (**blue**) [LRD 3069](#); - Work lamp with warning light (**orange**) [LRD 3068](#); - Work light with magnetic assemble base and cigarette lighter plug [LRD 3070](#); - Work lamp with handle and cigarette lighter plug [LRD 3071](#). All lighting products are made in **Poland** by [Horpol](#), which is one of the leading automotive lamp manufacturer.

