

LD 2175/GRAPHITE

STALK MARKER LIGHT LD 2175/GRAPHITE

DANE TECHNICZNE

| | | |
|---------------------------|-------------------|---|
| Light colour | Light group | Light category |
| white/amber/red | HOR 77AG | marker |
| Ingress protection rating | LED light | LED quantity |
| IP 68 | yes | 4 |
| Power rating | Supply voltage | Cable |
| 0,5/1,3 W | 12/24 V | 2×0,75 mm ² ; cable length 0,5 m |
| Side | Side marker light | Front clearance light |
| left | yes | yes |
| Rear clearance light | Arm | Operating temperature range |
| yes | yes | from -30°C to +50°C |

OPIS

LD 2175/GRAPHITE is a triple stalk marker light on a diagonal, long arm, designed to be mounted **on the left side of a vehicle**. Designed for use from small trailers to trucks and semi-trailers. The light from the **GRAPHITE** collection features a sleek, dark shade, combining modern design with functionality for excellent visibility. **LD 2175/GRAPHITE features:** – front position light (white light); – stalk marker light (orange light); – rear position light (red light); Operating at a universal voltage of **12/24 V**, the light is characterised by low energy consumption. The **light with a reflecting device** has been manufactured only with **branded LEDs**, which ensure a unique quality of illumination and add a visual appeal to the contour of a vehicle in motion. The high **IP 68** rating and the operating temperature range of **- 30 degrees C to + 50 degrees C** make it a top quality product. **Make sure you stay safe on the road! Discover the GRAPHITE collection of lights, a stylish solution for the automotive industry.**



Horpol
NIP:

